

COMMERCIAL FILTRATION

MEGACHAR SERIES MODEL 2850

1 ½" WATERLINE ** FLOW RATES 44 gpm -- 55 gpm PEAK

[BFF-1 MODEL is to be used when pH is below 6.8. BFF-2 MODEL is to be used when pH is 7.5 or higher and/or minimal TANNINS are present.]

MODEL#	BFF-1-2850/3.5	BFF-2-2850/3.5	BFF-3-2850/3.5	BFF-1-2850/4.5	BFF-2-2850/4.5	BFF-3-2850/4.5	BFF-1-2850/7.5	BFF-2-2850/7.5	BFF-3-2850/7.5
TANK	14" X 65"			16" X 65"			21" X 62"		
GAC	3.5 CUFT./TANK			4.5 CUFT./TANK			7.5 CUFT./TANK		
WEIGHT	300 lbs.			350 lbs.			490 lbs.		
MODEL#	BFF-1-2850/10			BFF-2-2850/10			BFF-3-2850/10		
TANK	24" X 71"								
GAC	10.0 CUFT./TANK								
WEIGHT	750 lbs.								

HFD-BFF-3 SERIES contain equal parts of SAND / AG / GAC

MEGACHAR SERIES MODEL 2900

2" WATERLINE ** FLOW RATES 84 gpm -- 105 gpm PEAK

[BFF-1 MODEL is to be used when pH is below 6.8. BFF-2 MODEL is to be used when pH is 7.5 or higher and/or minimal TANNINS are present.]

MODEL#	BFF-1-2900/3.5	BFF-2-2900/3.5	BFF-3-2900/3.5	BFF-1-2900/4.5	BFF-2-2900/4.5	BFF-3-2900/4.5	BFF-1-2900/7.5	BFF-2-2900/7.5	BFF-3-2900/7.5
TANK	14" X 65"			16" X 65"			21" X 65"		
GAC	3.5 CUFT./TANK			4.5 CUFT./TANK			7.5 CUFT./TANK		
WEIGHT	162 lbs.			300 lbs.			440 lbs.		

HFD-BFF-3 SERIES contain equal parts of SAND / AG / GAC

MEGACHAR SERIES MODEL 3900

3" WATERLINE ** FLOW RATES 210 gpm -- 271 gpm

[BFF-1 MODEL is to be used when pH is below 6.8. BFF-2 MODEL is to be used when pH is 7.5 or higher and/or minimal TANNINS are present.]

MODEL#	BFF-1- 3900/10	BFF-2- 3900/10	BFF-3- 3900/10	BFF-1- 3900/17	BFF-2- 3900/17	BFF-3- 3900/17	BFF-1- 3900/25	BFF-2- 3900/25	BFF-3- 3900/25
TANK	24" X 71"			30" X 72"			36" X 72"		
GAC	10 CUFT./TANK			17 CUFT./TANK			25 CUFT./TANK		
WEIGHT	660 lbs.			785 lbs.			1,140 lbs.		

HFD-BFF-3 SERIES contain equal parts of SAND / AG / GAC