

COMMERCIAL SOFTENING

High Flow Demand SODIALITE SYNCHROMATIC

HFD SERIES (1 ½" WATERLINE) -- FLOW RATES OF 37 gpm -- 48 gpm PEAK

MODEL #	HFD-SYN150K	HFD-SYN240K	HFD-SYN300K
TANK	16" X 65"	21" X 62"	24" X 71"
RESIN	5 CUFT. / TANK	8 CUFT. / TANK	10 CUFT. / TANK
BRINE	18" X 40"	24" X 48"	24" X 48"
WEIGHT	750 lbs.	1,320 lbs.	1,660 lbs.
CAPACITY	1,800,000 grains	2,880,000 grains	3,600,000 grains

MANIFOLD 2,3,4,5, or 6 UNITS FOR HIGHER FLOW RATES of NON INTERRUPTED SOFTENED WATER.

FOR EXAMPLE: HOTELS, HOSPITALS, LAUNDRIES...

COMMERCIAL FILTRATION

SYNCHROMATIC MEGACHAR High Flow Demand Carbon Filtration

HFD SERIES (1 ½" WATERLINE) -- FLOW RATES OF 37 gpm -- 48 gpm PEAK
 [BFF-1 MODEL is to be used when pH is below 6.8. BFF-2 MODEL is to be used when pH is 7.5 or higher and/or minimal TANNINS are present.]

MODEL#	HFD- BFF-1/5	HFD- BFF-2/5	HFD- BFF-3/5	HFD- BFF-1/7	HFD- BFF-2/7	HFD- BFF-3/7	HFD- BFF- 1/8.5	HFD- BFF- 2/8.5	HFD- BFF- 3/8.5
TANK	13" X 54"			14" X 65"			16" X 65"		
GAC	2.5 CUFT./TANK			3.5 CUFT./TANK			4.25 CUFT./TANK		
WEIGHT	200 lbs.			350 lbs.			450 lbs.		

MANIFOLD 2,3,4,5, or 6 UNITS FOR HIGHER FLOW RATES of NON INTERRUPTED SOFTENED WATER.

FOR EXAMPLE: HOTELS, HOSPITALS, LAUNDRIES...